

Paper



60 mm



Features

- 2 inches paper width
- Compact and light
- Print text, graphics and barcode
- Full control over printing quality/speed
- Integrated switches and LED (on-off line status, paper feed)
- 2 Communication ports
- Software programmable energy consumption
- Three resident fonts
- Downloadable character set
- Powerful Text Printing Modes
- Powerful Graphic Modes
- Hole/Mark Detection/Correct Paper Path Exit Detection
- Integrated cutter
- Easy firmware upgrades
- Multi position (3) Paper Roll support

Applications

- Kiosks
- Gas (Petrol) pumps
- Vending Machines
- Parking
- Bookings
- Multimedia Kiosks
- Public Offices
- Banking
- Self-Service

Specifications

KM290-HRS

Printing method	Thermal dot-line printing
Number of dots	432
Resolution (dots/mm)	8
Paper width (mm)	60
Printing width (mm)	54
Paper loading)	Automatic
Max. paper weight	100g/m ²
Printing speed (mm/s)	Up to 80
Paper roll diam. max. (mm)	140
Recommended Paper	JUJO AF50KS-E3, Koehler KT100P, Kanzan KPW460 or equivalent
Printing life	50Km/100M pulses
Cutter life	Min 500K cuts
Dimensions (WxHxD mm)	121x172x110 (according to the default paper holder ass.bly positions)
Weight (g)	700 approx.
Operating temperature (°C)	From -10 to +60 non cond.
Character set	3 resident + downloadable
Character size	8x16 / 7x16 / 12x20
Interfaces	RS232; USB (2.0)
Power supply	From 18V to 27V
Current Consumption (A)	From 1 to 8
Graphics	3 modes
Barcodes	UPC A-E, EAN 13-8, Code 39, ITF 2/5, Codabar, Code 128 A-B-C
Sensor	Near End Of Paper / End Of Paper / Head Up / Correct Paper path exit detection
Drivers	Windows - Linux
Label/Black mark detection	Y
Zero power mode (Sleep mode)	N
Auto wake-up on received data	N
Functional keyboard	Y