



HSP2208

Options

- Chipset UC32
- 300 dpi
- Controller Board
- 86 mm Paper Width
- Linerless

Features

- Heavy duty & compact
- Full easy loading (roll and cutter)
- Fast printing speed up to 300 mm per second
- Powerful cutter : full and partial for paper thickness from 63 to 190 μm / 2 million cuts
- Cuts paper up to 220 μm (10 mils) in less than 120 ms & 80 μm in less than 60 ms
- Black mark & paper end detection for label printing
- Very silent operation and high print quality

Applications

- ATM
- Gaming & Lottery
- Gas Pumps & Car Wash
- Kiosk
- Parking
- Ticketing
- Weighing Scales

Specifications	HSP2208-EL	HSP2208-KSL	HSP2208-KSR
Print method	Thermal	Thermal	Thermal
Number of dots	448	448	448
Resolution (dots/mm)	8	8	8
Max Printing speed (mm/s)	300	300	300
Print resolution (dpi)	200	200	200
Sensor	Paper End	Black Mark, Paper End	Black Mark, Paper End
Cutter Home Position	Mechanical Switch	Mechanical Switch	Mechanical Switch
Cutter Type	Full & Partial	Full & Partial	Full & Partial
Media Type	Ticket	Ticket	Ticket
Paper width (mm)	60 to 62.5	60 to 62.5	60 to 62.5
Printing width (mm)	56	56	56
Min. paper thickness (μm)	63	63	63
Max. paper thickness (μm)	190	190	190
Paper loading	Easy loading	Automatic	Automatic
Dimensions (WxDxH mm)	95 x 74 x 30	95 x 74 x 30	95 x 74 x 30
Weight (g)	250	250	250
Operating Voltage	24V	24V	24V
Voltage range (Logic/Head)	5V or 3.3V \pm 5% / 24V \pm 10%	5V or 3.3V \pm 5% / 24V \pm 10%	5V or 3.3V \pm 5% / 24V \pm 10%
Paper detection	Opto sensor	Opto sensor	Opto sensor
Temperature detection	Thermistor	Thermistor	Thermistor



HSP2208

Specifications	HSP2208-EL	HSP2208-KSL	HSP2208-KSR
Head-up or Cover-open detection	Mechanical switch	Mechanical switch	Mechanical switch
Connector Type	FPC	FPC	FPC
Operating temperature	From -20° to 70°C	From -20° to 70°C	From -20° to 70°C
Storage temperature	From -40° to + 80°C	From -40° to + 80°C	From -40° to + 80°C
Operating humidity	10% to 90% (no condensing)	10% to 90% (no condensing)	10% to 90% (no condensing)
TPH	200 km / 100M pulses	200 km / 100M pulses	200 km / 100M pulses
Cutter	2 million cuts	2 million cuts	2 million cuts
Certifications	ISO 9001:2015, ISO14001, ISO13485:2016 certified - RoHS compliant	ISO 9001:2015, ISO14001, ISO13485:2016 certified - RoHS compliant	ISO 9001:2015, ISO14001, ISO13485:2016 certified - RoHS compliant